EVINRUDE® E-TEC® ENGINE SPECIFICATIONS

Engine Model	E30DRS E30DRG E30DRSL E30DRGL E30DRGL E30GTEL E30DTSL E30DGTL E30DPSL E30DPGL
Colour	Graphite White
Engine Type	Inline 2-Cylinder E-TEC
Bore x Stroke - mm	76 x 64
Displacement - cc	577
Gear Ratio	2.15:1
Full Throttle RPM Range	5500-6000 RPM
Weight - kg	68 70 75 85 82 82 82
Starting	Rope Electric and Rope
Controls	Mechanical
Fuel Induction	E-TEC Direct Injection with stratified low RPM combustion mode
Alternator Output*	56 Amps Total / 15 Amps Net Dedicated
Steering	Tiller Remote
Trim Method	Manual Tilt Power Trim and Tilt
Trim Range	-4° to 16°
Tilt Range	65°
Shaft Length - in	15 20
Lubrication	Multi-Point Targeted Oiling
Oil Tank Capacity - L	1.6
Recommended Oil	Evinrude XD-100
Recommended Fuel	87 Octane
Warranty	5-Year Extended Limited Warranty**
Emissions Compliance	EPA 2013 / CARB 3 STAR / European Union
Integrated Features	Auto-winterization, no break-in period
Accessories	Electric start, tiller, flush kit



Variable Voltage Computer Controlled 56 Amp. Current amp calculated at 13.5 V.
 Net dedicated battery charging power output is 15 Amp.
 **BRP 5 YEAR (STANDARD 3 * 2) This Extended Limited Warranty Program adds 24 months of BRP Limited Warranty coverage beyond the standard 36 month BRP Warranty applicable to Evinrude authorized engines under special conditions (see the Evinrude 2017 catalog for more details). Offered only through BRP European Distribution SA and its authorized BRP dealers for Evinrude* outboard engines that are sold to residents of the European Union for recreational use only.

