≅RENEGADE® X® mr 1000R

HIGHLIGHTS

- Rotax® snorkeled V-Twin engine with relocated
 Torsional Trailing arm Independent (TTI) CVT intake and outlet
- Intelligent Throttle Control (iTC™) with riding Mudguards
- Front and rear FOX† PODIUM† 1.5 QS3
- 30-in. ITP Cryptid† tires
- 14-in. cast-aluminum beadlock wheels
- 3,000-lb (1,361 kg) WARN[†] winch with roller fairlead
- Front & central aluminum skid plate
- · Heavy-duty front and rear bumpers
- Continuously Variable Transmission (CVT) with Extra Low L-Gear
- Aluminum taper-profile handlebar with grab handle, wind deflectors ans square pad
- Tri-Mode Dynamic Power Steering (DPS™)

- rear suspension
- Multifunction digital gauge
- · Painted plastics for premium look
- X-package coloration, graphics and seat cover



Gold, Black & Can-Am Red

ENGINE	1000R
Туре	91 hp, Rotax 976 cc V-twin, snorkeled, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC TM) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / Extra Low L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE [‡] auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS	
Front Suspension	Arched double A-arm with front sway bar
Front Shocks	FOX† PODIUM† 1.5 QS3
Rear Suspension	Torsional Trailing arm Independent (TTI)
Rear Shocks	FOX† PODIUM† 1.5 QS3

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers

TIRES / WHEELS	
Front Tires	ITP Cryptid† 30 x 9 x 14 in. (76.6 x 22.9 x 35.6 cm)
Rear Tires	ITP Cryptid† 30 x 9 x 14 in. (76.6 x 22.9 x 35.6 cm)
Wheels	14-in, cast-aluminum beadlock

DIMENSIONS / C	APACITIES
LxWxH	224 x 127 x 131 cm
Wheelbase	129.5 cm
Ground Clearance	31.8 cm
Seat Height	93.3 cm
Dry Weight	450 kg
Rack Capacity	Rear: 16 kg
Storage Capacity	N/A
Towing Capacity	590 kg
Fuel Capacity	20.5 L

FEATURES			
Gauge	Multifunction Digital: Speedometer, tachometer, odometer,	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
	trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Lighting	240 W from 4 fender mounted projector beam headlamps (60 W) with tail light / brake light
		Seat	Standard
Winch	3,000-lb (1,361 kg) WARN winch with roller fairlead	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)
Protection	Front & rear bumpers Aluminum taper-profile handlebar with grab handle, wind deflectors and square pad Mudguards front & central aluminum skid plate		

		-	. W	N.	1	7/
NAV A	154	157		M		1/4
	1 1 1	I A Y		м		

Factory 2 years



