≅RENEGADE® X® xc 1000R

HIGHLIGHTS

- Rotax® V-twin engine
- Intelligent Throttle Control (iTC™) with riding modes
- Front and rear FOX† PODIUM† 1.5 RC2 shocks
- New arched double A-arm front suspension with front sway bar
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS™)
- 12-in. cast-aluminum beadlock wheels
- 25-in. ITP Holeshot† ATR tires
- Front & central skid plate

- Aluminum taper-profile handlebar with wind deflectors and square pad
- Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control
- Torsional Trailing arm Independent (TTI) rear suspension
- Visco-Lok[‡] QE auto-locking front differential
- Multifunction digital gauge
- X-package coloration, graphics and seat cover



Black, Grey & Sunburst Yellow

ENGINE	1000R	
Туре	91 hp, Rotax 976 cc V-twin, liquid cooled	
Fuel Delivery System	Intelligent Throttle Control (iTC TM) with Electronic Fuel Injection (EFI)	
Transmission	CVT, P / R / N / H / L, standard engine braking	
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential	
Power Steering	Tri-Mode Dynamic Power Steering (DPS)	

SUSPENSIONS		
Front Suspension	Arched double A-arm with front sway bar 23.3 cm travel	
Front Shocks	FOX† PODIUM† 1.5 RC2	
Rear Suspension	on Torsional Trailing arm Independent (TTI) 25.1 cm travel	
Rear Shocks	FOX† PODIUM† 1.5 RC2	

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers

TIRES / WHEELS	
Front Tires	ITP Holeshot ATR 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm)
Rear Tires	ITP Holeshot ATR 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm)
Wheels	12-in. cast-aluminum beadlock

DIMENSIONS / CAPACITIES			
LxWxH	218.4 x 121.9 x 124 cm		
Wheelbase	129.5 cm		
Ground Clearance	26.7 cm		
Seat Height	87.7 cm		
Dry Weight*	323 kg		
Rack Capacity	Rear: 16 kg		
Storage Capacity	N/A		
Towing Capacity	590 kg		
Fuel Capacity	20.5 L		

FEATURES			
Gauge	Multifunction Digital: Speedometer, tachometer, odometer, trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
		Lighting	240 W from 4 fender mounted projector beam headlamps (60 W) with tail light / brake light
		Seat	Standard
Winch	Prewired for available winch	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)
Protection	Front bumper, aluminum taper-profile handlebar with wind deflectors and square pad, Front & central skid plate		

WARRANTY		
Factory	2 years	

